



TELEHANDLER (ROUGH TERRAIN) - 17M REACH

Features

- 4 wheel drive and 4 wheel steer
- Selectable front, crab & coordinated steering modes
- Power assisted steering
- Deutz 55.4kW Stage V/Tier 4 Final diesel
- Auxiliary hydraulic circuit on the boom
- Variable speed hydrostatic drive
- Constant flow
- Fully enclosed cab with heater and aircon
- Proportional joystick
- Flashing beacon & Road lights
- Illuminated gauge and switch panels
- Comes with fork carriage



	Telehandler 16.4m
Half Day Rate	POA
Daily Rate	POA
Weekly Rate	POA
Monthly (per week)	POA
Long Term Rates	POA

Enquire about other attachments:

Material bucket/ Truss boom/ Auger/ Suction lifter



Specifications

SR1745

Max. Lift Height (A)	16.4 m
Max. Lift Capacity	4,535 t
Max. Forward Reach	12.6 m
Overall Width (B)	2.3 m
Stowed Height (C)	2.56 m
Length to Fork Face (D)	6.6 m
Wheel Base	2.95 m
Ground Clearance	350 mm
Overall Weight	12,18 t
Max. Drive Speed	30km/h
Raise/ Lower Time	16/ 10.8 sec
Hydraulic Flow (per minute)	120 l
Hydraulic Pressure	230 bar
Hydraulic Oil Capacity	150 l
Fuel Capacity	120 l
Outside Turning Radius	4.2 m
Tyres	445/65 - 22.5"
Power Source	Diesel Engine
Drive system	4 x 4

