



TELEHANDLERS (ROUGH TERRAIN) - GM REACH

Features

- 4 wheel drive and 4 wheel steer
- Selectable front, crab & coordinated steering modes
- Power assisted steering
- Power source Yanmar 52kW Stage V diesel
- Constant flow
- Fully enclosed cab
- Proportional joystick
- Flashing beacon
- Road lights
- Illuminated gauge and switch panels
- Fully enclosed cab with heater and aircon
- Comes with fork carriage

	Telehandler 6m
Half Day Rate	POA
Daily Rate	POA
Weekly Rate	POA
Monthly (per week)	POA
Long Term Rates	POA



Delivery

Pick Up

Enquire about other attachments:

Material bucket/ Jib lifter/ Auger

Suction panel lifter



Specifications

SR626

Max. Lift Height (A)	5.8 m
Max. Lift Capacity	2.6 t
Max. Forward Reach	3.2 m
Overall Width (B)	1.89 m
Stowed Height (C)	1.93 m
Length to Fork Face (D)	4.19 m
Wheel Base	2.5 m
Ground Clearance	220 mm
Overall Weight	4.7 t
Max. Drive Speed	30km/h
Raise/ Lower Time	6.9/ 5 sec
Hydraulic Flow (per minute)	70 l
Hydraulic Pressure	230 bar
Hydraulic Oil Capacity	70 l
Fuel Capacity	80 l
Outside Turning Radius	3.25 m
Tyres	12 x 16.5
Power Source	Diesel Engine
Drive system	4 x 4



Snorkel SR626 2021 model

